

MATERIAL SAFETY DATA SHEET

Product Trade Name:

NATIONAL® BENTONITE

Revision Date:

11-Jan-2005

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Trade Name:

NATIONAL® BENTONITE

Synonyms:

None Mineral

Chemical Family: Application:

Additive

Manufacturer/Supplier

BPM Minerals LLC

3000 N Sam Houston Parkway East

Houston, TX 77032

Telephone: (281) 871-7900

Fax: (281) 871-7940

Emergency Telephone: (800) 666-9260 or (713) 753-3000

Prepared By

Chemical Compliance

Telephone: 1-580-251-4335

2. COMPOSITION/INFORMATION ON INGREDIENTS

SUBSTANCE	CAS Number	PERCENT	ACGIH TLV-TWA	OSHA PEL-TWA
Crystalline silica, cristobalite	14464-46-1	0 - 1%	0.05 mg/m ³	1/2 x 10 mg/m³. %SiO2 + 2
Crystalline silica, tridymite	15468-32-3	0 - 1%	0.05 mg/m³	1/2 x <u>10 mg/m³</u> %SiO2 + 2
Crystalline silica, quartz	14808-60-7	1 - 5%	0.05 mg/m³	10 mg/m³ %SiO2 + 2
Bentonite	1302-78-9	60 - 100%	Not applicable	Not applicable

More restrictive exposure limits may be enforced by some states, agencies, or other authorities.

3. HAZARDS IDENTIFICATION

Hazard Overview

CAUTION! - ACUTE HEALTH HAZARD May cause eye and respiratory irritation.

DANGER! - CHRONIC HEALTH HAZARD

Breathing crystalline silica can cause lung disease, including silicosis and lung cancer. Crystalline silica has also been associated with scleroderma and kidney disease.

This product contains quartz, cristobalite, and/or tridymite which may become airborne without a visible cloud. Avoid breathing dust. Avoid creating dusty conditions. Use only with adequate ventilation to keep exposures below recommended exposure limits. Wear a NIOSH certified, European Standard EN 149, or equivalent respirator when using this product. Review the Material Safety Data Sheet (MSDS) for this product, which has been provided to your employer.

4. FIRST AID MEASURES

Inhalation

If inhaled, remove from area to fresh air. Get medical attention if respiratory irritation

develops or if breathing becomes difficult.

Skin

Wash with soap and water. Get medical attention if irritation persists.

Eyes

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes

and get medical attention if irritation persists.

Ingestion

Under normal conditions, first aid procedures are not required.

Notes to Physician

Treat symptomatically.

5. FIRE FIGHTING MEASURES

Flash Point/Range (F):
Flash Point/Range (C):
Flash Point Method:
Autoignition Temperature (F):
Autoignition Temperature (C):
Flammability Limits In Air - Lower (%):

Flammability Limits in Air - Upper (%):

Not Determined Not Determined Not Determined

Not Determined

Not Determined

Not Determined

Not Determined

Fire Extinguishing Media

All standard firefighting media.

Special Exposure Hazards

Not applicable.

Special Protective Equipment for Not applicable.

Fire-Fighters

NFPA Ratings: HMIS Ratings:

Health 0, Flammability 0, Reactivity 0 Flammability 0, Reactivity 0, Health 0*

6. ACCIDENTAL RELEASE MEASURES

Personal Precautionary Measures Use appropriate protective equipment. Avoid creating and breathing dust.

Environmental Precautionary

Measures

None known.

Procedure for Cleaning /

Absorption

Collect using dustless method and hold for appropriate disposal. Consider possible toxic or fire hazards associated with contaminating substances and use appropriate

methods for collection, storage and disposal.

NATIONAL® BENTONITE Page 2 of 7

HANDLING AND STORAGE

Handling Precautions This product contains quartz, cristobalite, and/or tridymite which may become

airborne without a visible cloud. Avoid breathing dust. Avoid creating dusty conditions. Use only with adequate ventilation to keep exposure below

recommended exposure limits. Wear a NIOSH certified, European Standard En 149.

or equivalent respirator when using this product. Material is slippery when wet.

Storage Information Use good housekeeping in storage and work areas to prevent accumulation of dust.

Close container when not in use. Do not reuse empty container.

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls Use approved industrial ventilation and local exhaust as required to maintain

exposures below applicable exposure limits listed in Section 2.

Respiratory Protection Wear a NIOSH certified, European Standard EN 149, or equivalent respirator when

using this product.

Hand Protection Normal work gloves.

Skin Protection Wear clothing appropriate for the work environment. Dusty clothing should be

laundered before reuse. Use precautionary measures to avoid creating dust when

removing or laundering clothing.

Eye Protection Wear safety glasses or goggles to protect against exposure.

Other Precautions None known.

PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Solid Color:

Various Odor: Odorless pH: 8-10 Specific Gravity @ 20 C (Water=1): 2.65

Density @ 20 C (lbs./gallon): **Not Determined**

Bulk Density @ 20 C (lbs/ft3): 50-70

Boiling Point/Range (F): Not Determined Bolling Point/Range (C): Not Determined Freezing Point/Range (F): Not Determined Freezing Point/Range (C): Not Determined Vapor Pressure @ 20 C (mmHg): Not Determined Vapor Density (Air≖1): Not Determined Percent Volatiles: **Not Determined** Evaporation Rate (Butyl Acetate=1): Not Determined

Solubility in Water (g/100ml): Insoluble Solubility in Solvents (g/100ml): Not Determined VOCs (lbs./gallon): Not Determined

Viscosity, Dynamic @ 20 C (centipoise): Not Determined Viscosity, Kinematic @ 20 C (centistrokes): Not Determined Partition Coefficient/n-Octanol/Water: Not Determined Molecular Weight (g/mole): Not Determined

10. STABILITY AND REACTIVITY

Stability Data: Stable

Hazardous Polymerization: Will Not Occur

> NATIONAL® BENTONITE Page 3 of 7

Conditions to Avoid

None anticipated

Incompatibility (Materials to

Avoid)

Hydrofluoric acid.

Hazardous Decomposition

Products

Amorphous silica may transform at elevated temperatures to tridymite (870 C) or cristobalite (1470 C).

Additional Guidelines

Not Applicable

11. TOXICOLOGICAL INFORMATION

Principle Route of Exposure

Eye or skin contact, inhalation,

Inhalation

Inhaled crystalline silica in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (IARC, Group 1). There is sufficient evidence in experimental animals for the carcinogenicity of tridymite (IARC, Group 2A).

Breathing silica dust may cause irritation of the nose, throat, and respiratory passages. Breathing silica dust may not cause noticeable injury or illness even though permanent lung damage may be occurring. Inhalation of dust may also have serious chronic health effects (See "Chronic Effects/Carcinogenicity" subsection below).

Skin Contact

May cause mechanical skin irritation.

Eye Contact

May cause eye irritation.

Ingestion

None known

Aggravated Medical Conditions

Individuals with respiratory disease, including but not limited to asthma and bronchitis, or subject to eye irritation, should not be exposed to quartz dust.

Chronic Effects/Carcinogenicity

Silicosis: Excessive inhalation of respirable crystalline silica dust may cause a progressive, disabling, and sometimes-fatal lung disease called silicosis. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness, and reduced pulmonary function. This disease is exacerbated by smoking. Individuals with silicosis are predisposed to develop tuberculosis.

Cancer Status: The International Agency for Research on Cancer (IARC) has determined that crystalline silica inhaled in the form of quartz or cristobalite from occupational sources can cause lung cancer in humans (Group 1 - carcinogenic to humans) and has determined that there is sufficient evidence in experimental animals for the carcinogenicity of tridymite (Group 2A - possible carcinogen to humans). Refer to IARC Monograph 68, Silica, Some Silicates and Organic Fibres (June 1997) in conjunction with the use of these minerals. The National Toxicology Program classifies respirable crystalline silica as "Known to be a human carcinogen". Refer to the 9th Report on Carcinogens (2000). The American Conference of Governmental Industrial Hygienists (ACGIH) classifies crystalline silica, quartz, as a suspected human carcinogen (A2).

There is some evidence that breathing respirable crystalline silica or the disease silicosis is associated with an increased incidence of significant disease endpoints such as scleroderma (an immune system disorder manifested by scarring of the lungs, skin, and other internal organs) and kidney disease.

Other Information

For further information consult "Adverse Effects of Crystalline Silica Exposure" published by the American Thoracic Society Medical Section of the American Luna Association, American Journal of Respiratory and Critical Care Medicine, Volume

155, pages 761-768 (1997).

Toxicity Tests

Oral Toxicity:

Not determined

Dermal Toxicity:

Not determined

Inhalation Toxicity:

Not determined

Primary Irritation Effect:

Not determined

Carcinogenicity

Refer to IARC Monograph 68, Silica, Some Silicates and Organic Fibres (June

1997).

Genotoxicity:

Not determined

Reproductive /

Not determined

Developmental Toxicity:

ECOLOGICAL INFORMATION

Mobility (Water/Soil/Air)

Not determined

Persistence/Degradability

Not determined

Bio-accumulation

Not Determined

Ecotoxicological Information

Acute Fish Toxicity:

TLM96: 10000 ppm (Oncorhynchus mykiss)

Acute Crustaceans Toxicity: Not determined Acute Algae Toxicity:

Not determined

Chemical Fate Information

Not determined

Other Information

Not applicable

DISPOSAL CONSIDERATIONS

Disposal Method

Bury in a licensed landfill according to federal, state, and local regulations.

Contaminated Packaging

Follow all applicable national or local regulations.

TRANSPORT INFORMATION

Land Transportation

DOT

Not restricted

Canadian TDG Not restricted

ADR Not restricted

NATIONAL® BENTONITE Page 5 of 7

Air Transportation

ICAO/IATA Not restricted

Sea Transportation

IMDG

Not restricted

Other Shipping Information

Labels:

None

REGULATORY INFORMATION

US Regulations

US TSCA Inventory

All components listed on inventory.

EPA SARA Title III Extremely Hazardous Substances

Not applicable

EPA SARA (311,312) Hazard Class

Acute Health Hazard Chronic Health Hazard

EPA SARA (313) Chemicals

This product does not contain a toxic chemical for routine annual "Toxic Chemical

Release Reporting" under Section 313 (40 CFR 372).

EPA CERCLA/Superfund

Not applicable. Reportable Spill Quantity For This

Product

EPA RCRA Hazardous Waste

Classification

if product becomes a waste, it does NOT meet the criteria of a hazardous waste as

defined by the US EPA.

California Proposition 65

The California Proposition 65 regulations apply to this product.

MA Right-to-Know Law

One or more components listed.

NJ Right-to-Know Law

One or more components listed.

PA Right-to-Know Law

One or more components listed.

Canadian Regulations

Canadian DSL Inventory

All components listed on inventory.

WHMIS Hazard Class

D2A Very Toxic Materials (Crystalline silica)

16. OTHER INFORMATION

The following sections have been revised since the last issue of this MSDS Not applicable

> **NATIONAL® BENTONITE** Page 6 of 7

Additional Information

For additional information on the use of this product, contact your local Halliburton representative.

For questions about the Material Safety Data Sheet for this or other Halliburton products, contact Chemical Compliance at 1-580-251-4335.

Disclaimer Statement

This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of the user.

END OF MSDS