



Marubeni

MATERIAL SAFETY DATA SHEET

Marubeni Special Chemicals Inc
8675 Hidden River Parkway Tampa, FL 33637
Phone: 813-972-5959 Fax: 800-640-1616

Emergency Phones

CHEMTREC: 800-424-9300

METHYL ETHYL KETONE

SECTION 1 – Chemical Product Information

Product name: Methyl ethyl ketone
Synonym: 2-Butanone
Chemical Name: Methyl Ethyl Ketone
Chemical Formula: C₄H₈O

SECTION 2 – Composition/Information on Ingredients

Name	CAS #	% by Weight
Methyl ethyl ketone	78-93-3	100

SECTION 3 – HAZARD IDENTIFICATION

Potential Acute Health Effects: Hazardous in case of skin contact (irritant, permeator), of eye contact (irritant), of ingestion, of inhalation (lung irritant).
Potential Chronic Health Effects: CARCINOGENIC EFFECTS: Not available. MUTAGENIC EFFECTS: Mutagenic for bacteria and/or yeast. TERATOGENIC EFFECTS: Classified POSSIBLE for human. DEVELOPMENTAL TOXICITY: Not available. The substance may be toxic to gastrointestinal tract, upper respiratory tract, skin, eyes, central nervous system (CNS). Repeated or prolonged exposure to the substance can produce target organs damage.

SECTION 4 – FIRST AID MEASURES

Eye Contact: Check for any remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Cold water may be used. Get medical attention.
Skin Contact: In case of contact, immediately flush skin with plenty of water. Cover the irritated skin with an emollient. Remove contaminated clothing and shoes. Cold water may be used. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention.
Serious Skin Contact: Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek medical attention.
Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Serious Inhalation: Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek medical attention.
Ingestion: Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention if symptoms appear.
Serious Ingestion: Not available.

SECTION 5 – FIRE FIGHTING MEASURES

Flammability of the Product:	Flammable
Auto-Ignition Temperature:	404°C (759.2°F)
Flash Points:	CLOSED CUP: -9°C (15.8°F). OPEN CUP: -5.5556°C (22°F) (Tag).
Flammable Limits:	LOWER: 1.8% UPPER: 10%
Products of Combustion:	These products are carbon oxides (CO, CO ₂).
Fire Hazards in Presence of Various Substances:	Highly flammable in presence of open flames and sparks, of heat.
Explosion Hazards in Presence of Various Substances:	Risks of explosion of the product in presence of mechanical impact: not available. Risks of explosion of the product in presence of static discharge: Not available. Explosive in presence of oxidizing materials, of acids.
Fire Fighting Media and Instructions:	Flammable liquid, soluble or dispersed in water. SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use alcohol foam, water spray or fog.
Special Remarks on Fire Hazards:	Ignition on contact with potassium t-butoxide. Vapor may cause a flash fire
Special Remarks on Explosion Hazards:	Reaction with Hydrogen Peroxide + nitric acid forms heat and shock-sensitive explosive product. Mixture with 2-propanol will produce explosive peroxides during storage.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Small Spill:	Dilute with water and mop up, or absorb with an inert dry material and place in an appropriate waste disposal container.
Large Spill:	Flammable liquid. Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not touch spilled material. Prevent entry into sewers, basements or confined areas; dike if needed. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities.

SECTION 7– HANDLING AND STORAGE

Precautions:	Keep locked up.. Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/vapor/spray. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as oxidizing agents, metals, acids, alkalis.
Storage:	Store in a segregated and approved area. Keep container in a cool, well-ventilated area. Keep container tightly closed and sealed until ready for use. Avoid all possible sources of ignition (spark or flame).

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls:	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash and safety showers are proximal to the work-station location.
Personal Protection:	Splash goggles. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.
Personal Protection in Case of a Large Spill:	Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient, consult a specialist BEFORE handling this product.
Exposure Limits:	TWA: 200 STEL: 300 (ppm) from ACGIH (TLV) [United States] [1999] TWA: 150 STEL: 300 (ppm) [Australia] TWA: 590 STEL: 885 (mg/m ³) from NIOSH TWA: 200 STEL: 300 (ppm) from NIOSH TWA: 590 STEL: 885 (mg/m ³) [Canada] TWA: 200 STEL: 300 (ppm) from OSHA (PEL) [United States] TWA: 590 STEL: 885 (mg/m ³) from OSHA (PEL) [United States] Consult local authorities for acceptable exposure limits.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Physical state and appearance:	Liquid.
Odor:	Acetone-like Pleasant. Pungent. Sweetish. (Strong.)
Taste:	Not available.
Molecular Weight:	72.12g/mole
Color:	Clear Colorless.
pH (1% soln/water):	Not available.
Boiling Point:	79.6 (175.3°F)
Melting Point:	-86°C (-122.8°F)
Critical Temperature:	262.5°C (504.5°F)
Specific Gravity:	0.805 (Water=1)
Vapor Pressure:	10.3 kPa (@ 20°C)
Vapor Density:	2.41 (Air=1)
Volatility:	Not available.
Odor Threshold:	0.25 ppm
Water/Oil Dist. Coeff.:	The product is more soluble in oil; log(oil/water)=0.3
Ionicity (in Water):	Not available.
Dispersion Properties:	See solubility in water, diethyl ether, and acetone.
Solubility:	Soluble in cold water, diethyl ether, acetone.

SECTION 10 – STABILITY AND REACTIVITY

Stability:	The product is stable.
Instability Temperature:	Not available.
Conditions of Instability:	Heat, ignition sources, mechanical shock, incompatible materials.
Incompatibility with various substances:	Reactive with oxidizing agents, metals, acids, alkalis.
Corrosivity:	Non-corrosive in presence of glass.
Special Remarks on Reactivity:	Incompatible with chloroform, copper, hydrogen peroxide, nitric acid, potassium t-butoxide, 2-propanol, chlorosulfonic acid, strong oxidizers, amines, ammonia, inorganic acids, isocyanates, caustics, pyridines. Vigorous reaction with chloroform +alkali.
Special Remarks on Corrosivity:	Not available.
Polymerization:	Will not occur.

SECTION 11 – TOXICOLOGICAL INFORMATION

Routes of Entry:	Absorbed through skin. Dermal contact. Eye contact. Inhalation.
Toxicity to Animals:	WARNING: THE LC50 VALUES HEREUNDER ARE ESTIMATED ON THE BASIS OF A 4-HOUR EXPOSURE. Acute oral toxicity (LD50): 2737 mg/kg [Rat]. Acute dermal toxicity (LD50): 6480 mg/kg [Rabbit]. Acute toxicity of the vapor (LC50): 32000 mg/m ³ 4 hours [Mouse].
Chronic Effects on Humans:	MUTAGENIC EFFECTS: Mutagenic for bacteria and/or yeast. TERATOGENIC EFFECTS: Classified POSSIBLE for human. May cause damage to the following organs: gastrointestinal tract, upper respiratory tract, skin, eyes, central nervous system (CNS).
Other Toxic Effects on Humans:	Hazardous in case of skin contact (irritant, permeator), of ingestion, of inhalation (lung irritant).
Special Remarks on Toxicity to Animals:	Not available.
Special Remarks on Chronic Effects on Humans:	May cause birth defects based on animal data. Embryotoxic and/or foetotoxic in animal.
Special Remarks on other Toxic Effects on Humans:	Acute Potential Health Effects: Skin: Causes skin irritation. May be absorbed though the skin. Eyes: Causes eye irritation. Inhalation: Inhalation of high concentrations may cause central nervous effects characterized by headache, dizziness, unconsciousness, and coma. Causes respiratory tract irritation and affects the sense organs. May affect the liver and urinary system. Ingestion: causes gastrointestinal tract irritation with nausea, vomiting and diarrhea. May affect the liver. Chronic Potential Health Effects: Chronic inhalation may

cause effects similar to those of acute inhalation. Prolonged or repeated skin contact may cause defatting and dermatitis.

SECTION 12 – ECOLOGICAL INFORMATION

Ecotoxicity: Ecotoxicity in water
(LC50): 3220 mg/l 96 hours [Fathead Minnow]. 1690 mg/l 96 hours [Bluegill].
BOD5 and COD: Not available.
Products of Biodegradation: Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.
Toxicity of the Products of Biodegradation: The product itself and its products of degradation are not toxic.
Special Remarks on the Products of Biodegradation: Not available.

SECTION 13 – DISPOSAL CONSIDERATIONS

Waste disposal: Waste must be disposed of in accordance with federal, state and local environmental control regulations.

SECTION 14 – TRANSPORT INFORMATION

D.O.T. Classification: CLASS 3: Flammable liquid.
Identification: Ethyl methyl ketone UNNA: 1193 PG: II
Special Provisions for Transport: Not available.

SECTION 15 – REGULATORY INFORMATION

Federal and State Regulations: New York release reporting list: Methyl ethyl ketone Rhode Island RTK hazardous substances: Methyl ethyl ketone Pennsylvania RTK: Methyl ethyl ketone Minnesota: Methyl ethyl ketone Massachusetts RTK: Methyl ethyl ketone New Jersey: Methyl ethyl ketone California Director's list of Hazardous Substances: Methyl ethyl ketone TSCA 8(b) Inventory: Methyl ethyl ketone TSCA 8(d) H and S data reporting: Methyl ethyl ketone: Effective: 10/04/82; Sunset: 10/4/92 SARA 313 toxic chemical notification and release reporting: Methyl ethyl ketone CERCLA: Hazardous substances.: Methyl ethyl ketone: 5000 lbs. (2268 kg)

Other Regulations: OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200). EINECS: This product is on the European Inventory of Existing Commercial Chemical Substances.

Other Classifications:
WHMIS (Canada): CLASS B-2: Flammable liquid with a flash point lower than 37.8°C (100°F). CLASS D-2A: Material causing other toxic effects (VERY TOXIC).
DSCL (EEC): R11-Highly flammable. R36/37 – Irritating to eyes and respiratory system. S9 – Keep container in a well-ventilated place. S16- Keep away from sources of ignition – No smoking. S25 – Avoid contact with eyes. S33 – Take precautionary measures against static discharges.

HMIS (U.S.A.):
Health Hazard: 2
Fire Hazard: 3
Reactivity: 0
Personal Protection: h

National Fire Protection Association (U.S.A.):
Health: 1
Flammability: 3
Reactivity: 0
Specific hazard:
Protective Equipment: Gloves. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate. Splash goggles.

SECTION 16 – OTHER INFORMATION

Supplier MSDS Date: 11/30/2011

This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of Marubeni Specialty Chemicals Inc acknowledgement or obtained from sources believed by Marubeni Specialty Chemicals Inc to be accurate, and Marubeni Specialty Chemicals Inc. does not assume any legal responsibility for use or reliance upon same. Customers are encouraged to conduct their own tests. Before using any product, read its label.