



MATERIAL SAFETY DATA SHEET

SECTION 1 – PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: PYROZOL KCC 351
PRODUCT CODE:
GENERAL USE: TEXTILE FLAME RETARDANT

EMERGENCY TELEPHONE: 800-786-4633

MANUFACTURER: ISOCHEM COLORS, INC.
 138 BEERAN ST.
 CLOVER, SC 29710

CUSTOMER SERVICE:
 (800) 786-4633

SECTION II – COMPOSITION/INFORMATION ON INGREDIENTS

<u>COMPONENT NAME</u>	<u>CAS NO.</u>	<u>%</u>	<u>OSHA</u>	<u>ACGIH (TLV)</u>	<u>CARCINOGEN</u>
TETRAKIS (HYDROXYMETHYL) PHOSPHONIUM CHLORIDE UREA PRECONDENSATE	27104-30-9	66 - 70	N / E	N/E	-
FORMALDEHYDE	50-00-0	<0.03	0.75 ppm 2 ppm STEL	0.3ppm (CEILING)	NTP IARC-1 OSHA ACGIH A2

SECTION III HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: NO HAZARD IN NORMAL INDUSTRIAL USE. USE GOOD HYGIENIC PRACTICES.
APPEARANCE: LOW VISCOSITY STRAW LIQUID
ODOR: PUNGENT

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM (HMIS) RATING:
 HEALTH: 3 FLAMMABILITY: 1 REACTIVITY: 0 PERSONAL PROTECTION: D

POTENTIAL HEALTH EFFECTS

EYE CAUSES EYE BURNS
 SKIN CONTACT MAY CAUSE ALLERGIC SKIN REACTION
 INGESTION MAY BE HARMFUL IF SWALLOWED OR ABSORBED THROUGH SKIN.
 INHALATION MAY BE HARMFUL IF INHALED
 TARGET ORGANS NO KNOWN EFFECTS.

EFFECTS OF EXPOSURE:

ACUTE ORAL LD50 (RAT) AND DERMAL (RABBIT) LD50 VALUES ARE 200 - 500 MG/KG AND ~2,000 MG/KG, RESPECTIVELY. THE 4-HOUR INHALATION LC50 (RAT) VALUE IS 0.59 MG/L. THIS MATERIAL CAUSED MINIMAL SKIN AND SEVERE EYE IRRITATION WHEN TESTED IN RABBITS. IT WAS NOT MUTAGENIC IN THE AMES SALMONELLA ASSAY. SKIN SENSITIZATION WAS PRODUCED IN STUDIES WITH GUINEA PIGS ACCORDING TO LITERATURE.

SECTION IV – FIRST AID MEASURES

EYES: IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. IF NECESSARY, SEEK MEDICAL ATTENTION.
SKIN: FOR SKIN CONTACT, WASH IMMEDIATELY WITH SOAP AND WATER. IF NECESSARY, SEEK MEDICAL ATTENTION.
INGESTION: IF THE MATERIAL IS SWALLOWED, GET IMMEDIATE MEDICAL ATTENTION OR ADVICE.
INHALATION: IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION, PREFERABLY MOUTH-TO-MOUTH. IF BREATHING IS DIFFICULT, GIVE OXYGEN.

SECTION V – FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

FLASH POINT: 215°F
METHOD: SETAFLASH CLOSED CUP
UPPPER FLAMMABLE LIMIT: NOT DETERMINED
LOWER FLAMMABLE LIMIT: NOT DETERMINED
FLAMMABILITY CLASSIFICATION: CLASS IIIB

HAZARDOUS PRODUCTS OF COMBUSTION

UPON DECOMPOSITION, CABON MONOXIDE, CARBON DIOXIDE, OXIDES OF SULFER, OXIDES OF PHOSPHOROUS, FORMALDEHYDE, PHOSPHINE GAS, ORGANOPHOSPHINE VAPORS, HYDROGEN.

PROPERTIES THAT COULD INCREASE FIRE OR EXPLOSION

NO KNOWN HAZARDS.

EXTINGUISHING MEDIA

FOAM (PREFERRED), DRY CHEMICAL, WATER.

FIRE FIGHTING INSTRUCTIONS

FIREFIGHTERS SHOULD WEAR FULL PROTECTIVE CLOTHING INCLUDING SELF CONTAINED BREATHING APPARATUS.

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) RATING

HEALTH: 3 FLAMMABILITY: 1 REACTIVITY: 0 SPECIAL

SECTION VI - ACCIDENTAL RELEASE MEASURES

SMALL SPILL

CONTAINMENT TECHNIQUES: DIKE THE SPILLED MATERIAL, WHERE THIS IS POSSIBLE.

CLEANUP PROCEDURES: COLLECT THE SPILLED MATERIAL WITH AN INERT ABSORBENT SUCH AS SAND OR VERMICULITE. PLACE IN PROPERLY LABELED CLOSED CONTAINER.

EQUIPMENT: SHOVEL THE MATEIRAL INTO WASTE CONTAINER.

OTHER EMERGENCY ADVICE: NO OTHER SPILL PROCEDURES NECESSARY.

LARGE SPILL

CONTAINMENT TECHNIQUES: DIKE THE SPILLED MATERIAL, WHERE THIS IS POSSIBLE.

CLEANUP PROCEDURES: NO OTHER SPILL PROCEDURES NECESSARY.

EQUIPMENT: NO ADDITIONAL INFORMATION ON EQUIPMENT.

OTHER EMERGENCY ADVICE: CAUTION! IF PRODUCT IS ABSORBED ON PAPER OR CLOTH, ARRANGE FOR DISPOSAL BY INCINERATION PROMPTLY TO PREVENT SPONTANEOUS COMBUSTION.

EVACUATION PROCEDURE

EVACUATE THE AREA PROMPTLY AND KEEP UPWIND OF THE SPILLED MATERIAL. ISOLATE THE SPILL AREA TO PREVENT PEOPLE FROM ENTERNING.

SECTION VII – HANDLING AND STORAGE

HANDLING: DO NOT GET THIS MATERIAL IN YOUR EYES, ON YOUR SKIN, OR ON YOUR CLOTHING.
STORAGE: KEEP THIS MATERIAL IN A COOL, DARK, WELL-VENTILATED PLACE.

SECTION VIII – EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS

PROVIDE ADEQUATE LOCAL EXHAUST VENTILATION TO MAINTAIN WORKER EXPOSURE BELOW EXPOSURE LIMITS.

PERSONAL PROTECTIVE EQUIPMENT

EYE/FACE PROTECTION: WEAR CHEMICAL GOGGLES OR A FULL FACE SHIELD.
HAND PROTECTION: USE IMPERVIOUS GLOVES.
SKIN PROTECTION: NORMAL WORK CLOTHING (LONG SLEEVED SHIRTS AND LONG PANTS) IS RECOMMENDED.
RESPIRATORY PROTECTION: A RESPIRATORY PROTECTION PROGRAM THAT MEETS OSHA'S 29 CFR 1910.134 AND ANSI Z88.2 REQUIREMENTS MUST BE FOLLOWED WHENEVER THERE MAY BE POTENTIAL FOR AIRBORNE EXPOSURE.

SECTION IX – PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: STRAW, LOW VISCOSITY LIQUID, PUNGENT ODOR
BOILING POINT: 224°F
FREEZING POINT: NOT AVAILABLE
PERCENT VOLATILE: 30 - 34 (WATER)
pH: 1% IN WATER : 3.5 – 4.5
SOLUBILITY IN WATER: COMPLETE
SPECIFIC GRAVITY: 1.28 – 1.30 @ 25°C
SPECIFIC DENSITY: NOT AVAILABLE

SECTION X – STABILITY AND REACTIVITY

STABILITY: STABLE UNDER NORMAL CONDITIONS.

CONDITIONS TO AVOID: AVOID EXCESSIVELY HIGH TEMPERATURES AND CONTACT WITH ALKALIES OR STRONG OXIDIZING AGENTS. UNSTABLE AT HIGH pH. Will OXIDIZE RELEASING FLAMMABLE HYDROGEN GAS.

HAZARDOUS REACTIONS: NONE KNOWN

SECTION XI – TOXICOLOGICAL INFORMATION

ACUTE EFFECTS

EYE EFFECTS: THIS PRODUCT CAUSES EYE BURNS.
SKIN EFFECTS: THIS PRODUCT MAY CAUSE ALLERGIC SKIN REACTION.
ACUTE ORAL EFFECTS (INGESTION): MAY BE HARMFUL IF INGESTED OR ABSORBED THROUGH THE SKIN.
ACUTE INHALATION EFFECTS: MAY BE HARMFUL IF INHALED.
SUBCHRONIC EFFECTS: NO KNOWN EFFECTS.

CHRONIC EFFECTS

TERATOLOGY: NO DATA AVAILABLE FOR THIS PRODUCT.
REPRODUCTIVE AND DEVELOPMENTAL TOXICITY: NO INFORMATION AVAILABLE.

ACUTE ORAL TOXICITY

ORAL LD50 RAT 200 - 500 MG/KG

OTHER TOXICOLOGICAL INFORMATION

DERMAL, RABBIT, LD50 ~2,000 MG/KG

FORMALDEHYDE HAS ORAL (RAT) AND DERMAL (RABBIT) LD50 VALUES OF 100 MG/KG AND 270 MG/KG, RESPECTIVELY. THE LC50 FOLLOWING A 4-HOUR INHALATION EXPOSURE TO RATS IS 250-478 PPM (0.31-0.59 MG/L). IRRITATION OF THE NOSE AND THROAT HAS BEEN OBSERVED IN PEOPLE EXPOSED TO FORMALDEHYDE VAPOR LEVELS IN EXCESS OF 1 PPM. NORMAL BREATHING MAY BE SERIOUSLY IMPAIRED AT LEVELS ABOVE 10 PPM AND SERIOUS LUNG DAMAGE CAN OCCUR AT LEVELS EXCEEDING 50 PPM. FORMALDEHYDE HAS BEEN REPORTED TO CAUSE PULMONARY HYPERSENSITIVITY IN SOME INDIVIDUALS WHO WERE EXPOSED TO CONCENTRATIONS NOW TO CAUSE IRRITATION; HOWEVER, NO PULMONARY SENSITIZATION HAS BEEN DEMONSTRATED IN LABORATORY ANIMAL STUDIES. FORMALDEHYDE SOLUTIONS CAN CAUSE SEVERE EYE AND MODERATE SKIN IRRITATION. REPEATED SKIN EXPOSURE TO SOLUTIONS OF 2% OR MORE FORMALDEHYDE HAS CAUSED ALLERGIC SKIN REACTIONS. FORMALDEHYDE WAS FOUND TO BE WEAKLY MUTAGENIC IN A NUMBER OF IN VITRO GENOTOXICITY TESTS AND POSITIVE IN CERTAIN IN VIVO SCREENING TESTS FOR MUTAGENICITY. FORMALDEHYDE DID NOT CAUSE BIRTH DEFECTS IN RATS INHALING CONCENTRATIONS UP TO 10 PPM. HOWEVER, A STUDY USING HIGHER LEVELS DID SHOW A SLIGHT BUT STATISTICALLY SIGNIFICANT REDUCTION IN MALE FETAL BODY WEIGHT. LIFETIME INHALATION OF FORMALDEHYDE VAPOR AT CONCENTRATIONS ABOVE 5 PPM FOR 6 HOURS PER DAY, CAUSED NASAL TUMORS IN LABORATORY ANIMALS. THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC) HAS CLASSIFIED

FORMALDEHYDE AS A GROUP 1 (KNOW) HUMAN CARCINOGEN BASED ON EPIDEMIOLOGICAL EVIDENCE LINKING FORMALDEHYDE EXPOSURE TO THE OCCURRENCE OF NASOPHARYNGEAL CANCER, A RARE TYPE OF CANCER. IARC ALSO FOUND LIMITED EVIDENCE OF CANCER OF THE NASAL CAVITY AND PARANASAL SINUSES AND INSUFFICIENT EVIDENCE FOR AN ASSOCIATION BETWEEN FORMALDEHYDE AND LEUKEMIA. INHALATION CAUSED LIVER AND KIDNEY DAMAGE IN LABORATORY ANIMAL TESTS.

SECTION XII – ECOLOGICAL INFORMATION

MOBILITY	NO INFORMATION AVAILABLE.
PERSISTENCE/DEGRADABILITY	NO INFORMATION AVAILABLE.
BIOACCUMALATION	NO INFORMATION AVAILABLE.
AQUATIC TOXICITY	THIS MATERIAL COULD BE HARMFUL TO AQUATIC LIFE IN HIGHER CONCENTRATIONS.

SECTION XIII – DISPOSAL CONSIDERATIONS

WASTE DESCRIPTION:	WASTE MUST BE TESTED USING METHODS DESCRIBED IN 40 CFR PART 261 TO DETERMINE IF IT MEETS APPLICABLE DEFINITIONS OF HAZARDOUS WASTES.
GENERAL DISPOSAL:	CLEAN UP AND DISPOSE OF WASTE IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL ENVIRONMENTAL AGENCIES.

SECTION XIV – TRANSPORTATION INFORMATION

DOT SHIPPING INFORMATION

PROPER SHIPPING NAME:	TOXIC LIQUID, ORGANIC, N.O.S.
TECHNICAL NAME (IF N.O.S. DESCRIPTION)	CONTAINS ORGANIC PHOSPHONIUM SALT
UN/NA NUMBER:	UN2810
HAZARD CLASS:	6.1
PACKING GROUP:	III
EMERGENCY RESPONSE GUIDE BOOK:	153
PLACARDS/LABELS REQUIRED:	TOXIC

INTERNATIONAL INFORMATION

	PROPER SHIPPING NAME
IMO	TOXIC LIQUID, ORGANIC, N.O.S.
IATA/ICAO	TOXIC LIQUID, ORGANIC, N.O.S.
MARINE POLLUTANT	YES

SECTION XV – REGULATORY INFORMATION

TOXIC SUBSTANCES CONTROL ACT:	THIS PRODUCT IS LISTED ON THE US EPA TSCA INVENTORY.		
TSCA EXPORT NOTIFICATION:	NO LIMITS ESTABLISHED FOR THIS PRODUCT.		
SECTION 311/312 CLASSIFICATION :	THIS PRODUCT HAS BEEN REVIEWED FOR SARA TITLE III. SECTION 313 AND IS NOT REPORTABLE.		
OSHA HAZARD CLASS:	ACUTE: YES PRESSURE: NO	CHRONIC: NO REACTIVITY: NO	FIRE HAZARD: NO

INFORMATION PREPARED: MAY 22, 2013

FOR FURTHER INFORMATION, CALL **ISOCHEM COLORS** 803-222-8500. THE INFORMATION AND RECOMMENDATIONS CONTAINED IN THIS MSDS SHEET ARE BASED UPON DATA BELIEVED TO BE CORRECT. NO GUARANTEE IS GIVEN, IMPLIED OR EXPRESSED FOR THIS DATA. **THIS SUPERSEDES ANY PREVIOUS MSDS SHEET.**